

## IN AHU & IN DUCT DISINFECTION

Our light commercial and residential in-duct UV fixtures provide a solution for disinfection throughout homes and businesses. The FCU (Fan Coil Unit) series is designed for applications where non-central HVAC systems exist, such as classrooms, hotel rooms, and older buildings. Benefits include:

- Engineered to maintain high level air disinfection 24/7 by neutralizing and eliminating the infectious airborne pathogens that cause respiratory illness and disease.
- Designed to achieve disinfection of the cooling coil surfaces to increase efficiency and decrease biological growth on the coil.
- Available in a range of configurations to accommodate various coil lengths or plenum spaces.e

### Models

There are six FCU models available using either 35W, 60W or 95W Philips PL-L UV lamps.

Designed to disinfect air and surfaces in non-central A/C & heating units.



Work 24/7 to keep air and units free and clear of airborne contaminants.



Neutralizes and eliminates the infectious airborne pathogens that cause respiratory illness and disease.



Provides a solution for disinfection throughout homes and businesses.

# **FCU Series**

## IN AHU & IN DUCT DISINFECTION

## **FCU Product Specifications**

Standard Specifications						
Lamp Specs			PL-L 35W, 60W, 95W TUV (non proprietary)			
Wavelength			254 Nanometers*			
Expected Lamp/Bulb Rated Life <sup>1</sup>			18 months			
Lamp Socket			Single Ended, 4 Pin, 2G12			
Input Voltage			Self Regulated Electronic UV Ballast 120V			
Electrical Requirement			See Ordering Guide			
Housing Finish			Aluminum			
Certifications:						
A THE ST	ASHRAE	meets	ASHRAE TC 2.09			
	EPA <sup>2</sup>	EST. N	O. 91347-TN-001			
	ETL	CDR10	00230620ATL-001A			

With 80% utilization <sup>2</sup>The manufacturer is registered with the US EPA. Clinical lab testing has been performed in independent labs.

TYPICAL FRONT VIEW FCU-235/260 42.25" (60W LAMP) 26.25" (35W LAMP) 10.500" \_\_\_\_LUMALIER SOCKETS RECESSED SAFETY SWITCH (inside) 0 0 PL-L35WTUV LAMPS PL-L60WTUV LAMPS WIRING CHAMBER MOUNTING HOLES TYPICAL TOP VIEW FCU-235/260 9 FT. CORD WITH PLUG (plug not shown) SAFETY SWITCH (inside)

Lamps/2 years; Parts/5 years

Due to continuing research, Lumalier reserves the right to change specifications without notice.

Ordering Guide					
Model#	Description	AHU	Size		
FCU-135	One 35 W, chill-corrected lamp, 360° disinfection	Coil width: 39" to 44 "	Total length = 37"		
FCU-160	One 60 W, Chill-corrected lamp, 360° disinfection	Coil width: 39" to 44 "	Total length = 37"		
FCU-195	One 95 W, chill-corrected 20" lamp, 360° disinfection	Coil width: 39" to 44"	Total length = 32"		
FCU-235	Two 35 W, chill-corrected lamps, 360° disinfection	Coil width: 30" to 38"	Total length = 28"		
FCU-260	Two 60 W, chill-corrected lamps, 360° disinfection	Coil width: 44" >	Total length = 42"		
FCU-295	Two 95 W, chill-corrected 20" lamps, 360° disinfection	Coil width: 48" >	Total length = 48"		



**ELUMALIER** www.lumalier.com 1931 Thomas Road | Memphis TN 38134 | 901-800-1709 or 1-888-610-1709

Warranty